



Physical:  
 Housing: LCP UL 94V-0  
 Contact: Selective Gold Flash  
 Specifications:  
 Voltage Current rating: 1A, 50V AC  
 Insulation Resistance: 1000Mohm Min  
 Contact Withstanding Voltage:  
 AC 500V For 1 Minute  
 Temperature Rating: -40° To +85°

ORDER INFORMATION:  
 SIMMP-00 X 01 B2 X X - G  
 6:6PIN  
 8:8PIN  
 0:TRAY  
 1:7&R  
 0:W/O Locating peg  
 1:With Locating peg  
 COMPLY TO RoHS

REV	MODIFICATION	DATE	DRAW
D	EN-07-0622	96/06/25	SAN
E	EN-08-0109	97/01/09	SAN
F	EN-08-0203	97/02/13	SAN

DIMENSION IN mm [Inch]	PROD. SPEC.	PROJ. SHEET 1
TOLERANCE UNLESS OTHERWISE SPECIFIED		
.X±0.25	APPROVE <i>Garry</i>	DWG NO. SIMMP-00X01B2XX-G
.XX±0.15	CHECK <i>Tony</i>	TITLE SIM CARD ACCEPTOR
.XXX±0.10	DRAW <i>Sam/13</i>	FILE NO.
		SIZE A4
		SCALE 2.5:1 REV F

KINGFONT PRECISION INDUSTRIAL CO., LTD.

CUSTOMER DRAWING