



REV	MODIFICATION	DATE	DRAW
B	EN-06-1125	95/11/27	TERENCE

Specification:

- * Withstanding Voltage: 500V DC /1M.
- * Insulation Resistance: 1000M Ohm
- * Voltage Rating: 5V AC
- * Current Rating: 0.5A/Product Max.
- * Contact Resistance: 60m Ohm Max.
- * Operating Temperature: $-25^{\circ}\text{C} \sim +85^{\circ}\text{C}$
- * Insertion Cycles: 10000 Times Min
- * Press Force: 0.2N~0.6N

Material and Finish:

- * Housing: LCP+30%G.F. UL 94V-0, Black
- * Contact: Copper Alloy
- * Contact Area: Gold Plating All Over Ni

DIMENSION IN mm [Inch]		PROD. SPEC.	TITLE	
TOLERANCE UNLESS OTHERWISE SPECIFIED		PKG. SPEC.	SIM CARD CONN. PUSH-IN/OUT	
.X \pm 0.30	X.* \pm	APPROVE	SMT TYPE	
.XX \pm 0.20	.X.* \pm	CHECK	FILE NO. SIM-KF016	DWG NO. BTX0
.XXX \pm 0.10	.XX.* \pm	DRAW	SIZE A4	PROJ. SHEET 1 / 1
			SCALE 2:1	REV B