



**HOLE LAYOUT
(BOTTOM VIEW)**

SPECIFICATION:

1. CURRENT CARRYING CAPACITY: 1) AC: 100V 1A MAX.
2) DC: 12V 2A MAX.
2. CONTACT RESISTANCE: 30m OHM MAX.
3. INSULATION RESISTANCE: 50M OHM MIN. AT DC 250V
4. VOLTAGE WITHSTANCE: AC 250V 1 MINUTE.
5. INSERTION FORCE : 1.0KGS - 4.5KG
WITHDRAWAL FORCE: 0.8KGS - 3.0KG

ARRANGEMENT OF CONTACTS							P/N	PART NAME	Q'TY	MATERIAL	PLATING	REMARKS
NO OF CONTACTS	3	4	5	6	7	8	4.	CONTACT TERMINAL	3~8	PBR-H 0.2t	SILVER PLATED	
MODEL NO	MDC-323	MDC-324	MDC-325	MDC-326	MDC-327	MDC-328	3.	EARTH TERMINAL	1	BRASS 0.3t	Pb10%, Sn90%	
HOLE LAYOUT							2.	COVER	1	VALOX-DR48	BLACK COLOR	UL94V-0
							1.	BODY	1	VALOX-DR48	BLACK COLOR	UL94V-0